

Creto Worldwide, Inc.

Po box 72795 Las Vegas, NV 89119 (800) 798-5807 fax (702) 798-5802

MATERIAL SAFETY DATA SHEET

TopSeal

PRODUCT IDENTIFICATION

TOPSEAL
(TS)

Emergency Telephone 1-877-832-9861

Hazard Rating

4 – Extreme

3 – High

2 – Moderate

1 – Slight

0 – Insignificant

Fire

Health

Reactivity

Special Hazard

0

1

0

0

Chemical Identity Information

CHEMICAL COMPOSITION

TRADE NAME: TOPSEAL

USEFULNESS: Waterproofing for Concrete

COMPONENT: Trade Name TS

Chemical Name:

Siliconate

Water

CAS NO.

31795-24-1 (30%)

7732-18-5 (70%)

Physical Data

Appearance:

Odor:

Boiling Point::

Specific Gravity:

Vapor Pressure:

Solubility in Water:

PH (1% solution):

Clear Liquid

None

212°F

1.04

Unknown

Complete

10.85

Fire and Explosion Data

Flash Point (Test Method):

Flammability or Explosive Limits:

Extinguishing Media:

Non-Flammable

Not Applicable

Not Applicable

Unusual Fire & Explosion Hazard:

Special Firefighting Procedures:

None

None

Reactivity

Stability:

Hazardous Decomposition Products:

Incompatible Materials:

Stable

None Known

Do not mix with other chemicals

Conditions to Avoid:

Hazardous Polymerization:

None

Will not occur

TopSeal

Health Hazard Data and First Aid Procedures

Contains no hazardous materials as defined by OSHA and ACGIH

ACGIH Threshold Limit Value:	Not established for mixture
Carcinogen – NPT Program:	No
Carcinogen – LARC Program:	No
Chronic Health Hazards:	None Known

Eyes:	May cause irritation and redness. Flush with cool, clean water for at least 15 minutes. If irritation persists, get medical attention.
Skin:	May cause redness. Flush with water, as above.
Ingestion:	Non-toxic, may cause gastro-intestinal problem. Do not induce vomiting. Dilute with large amounts of water and weak vinegar or orange juice. Get medical attention immediately.

Special Protection Information

Protective Gloves:	Rubber gloves recommended.
Eye Protection:	Safety goggles recommended.
Respiratory Protection:	None
Local Exhaust:	Good ventilation.

Spill or Leak Procedures

With small spills or leaks use absorbent material such as a sawdust, vermiculite or sand. Larger spills dilute with large amount of water, before flushing to a sewer or drain according to local, provincial or federal regulations.

Special Information

Keep container closed when not in use.
Store away from heat and do not freeze.
Keep out of reach of children.

www.creto.net